



Technical Data Sheet





SPECIFICATIONS		
Model		SX1255DV434
Application		Chassis
Drive System		6 x 4
Overall Length mm)		9,900
Overall Width (mm)		2,630
Overall Height (mm)		3,450
Wheelbase (mm)		4,375 + 1,400
Frame (mm)		850 x 300 (8 + 5)
Maximum Speed (Km/h)		92
Maximum Gradeability (%)		27%
Gear Box Model		FAST 12JSD200T-B with QH 50 PTO
Gears		12 Forwards & 2 Reserve Shifts
Cooling T	ype	Tropical Type, Radiator with Grille
Tyres Type	e	12.00R24, 11 tires Including One Spare Tire
Fuel Tank	Capacity (L)	600 L
Air filter		Oil Bath Air Filter
Emergency Brake system		WABCO ABS
Floorwise-	Туре	24V
Electrics	Battery	2*165 Ah

WEIGHT		
Complete Kerb Mass (Kg)	9,400	
Max Load (Kg)	35,000	

ENGINE		
Brand	Weichai	
Model	WP12.430 E201 4 Inlet Valve	
Power (KW/HP)	316/430	
Output Torque (N.m /rpm)	2000/1400	
Emission Standard	Euro II	

BRAKES	
Туре	Drum
Service Brake	Dual-circuit Compressed Air Brake
Park Brake	Power Spring Brake Acting on Rear Wheel
Auxiliary Brake	WEVB

Two	Main Films Plus Two U Bolts
Front	Longitudinal Leaf Springs (10 pcs)
Rear	Trapezoidal Leaf Spring (12 pcs)

SUSPENSION

AXLES	
Brand	Hande
Front Axle	MAN 9,500 kg
Rear Axle	MAN 2 x 16,000 kg Double-stage widened reduction axle with inter-wheel differential & differential lock
Ratio	4.769

CABIN	
Туре	SHACMAN F3000 Lengthened Flat Roof with Top Deflector
Equipment	Tropical Type A/C Tropical Type Hoses One Sleeper Heat Preservation Cabin One Sleeper Hydraulic Driver Seat with Seat Belts Hydraulic Suspension Cabin Manual Cab Flipping Manual Window Shaker Water Tank Protection Grid Headlights & Rear Lights Grilles 32T Jack Anti-theft Equipment for Battery Anti-theft Equipment for Fuel Tank Steel Plate Bumper One more Oil Filter