

TAKE YOUR BUSINESS TO NEW HEIGHTS.











4 Wheel Drive All Terrain Capability



2YEAR STANDARD WARRANTY OR 4000 HOURS













Available Variants

2DX 4WD, Engine Power 49hp, GP Shovel, Bucket - 0.18 cu.m



3DX 4WD, Engine Power 76hp, GP Shovel, Bucket -0.26 cu.m



SPECIFICATION: 3DX PLUS BACKHOE LOADER

ENGINE

JCB 444, 68.6 kW (92hp) Engine, turbocharged, 4 cylinder, water cooled, diesel engine 408Nm @1200rpm.

TRANSMISSION

JCB Synchro-shuttle transmission: It provides superb drive power in all conditions. It consists of a 4-speed, full synchromesh gearbox with integral torque convertor and electrically operated reversing power shuttle.

HYDRAULIC PUMP FLOW

123 LPM @ 2000 rpm

HYDRAULIC PRESSURE

3300 p.s.i.

BRAKES

Hydraulically actuated dual line, self adjusting, oil immersed, multi-disc type on the rear axle, well protected from dirt, water etc. requiring no maintenance.

STEERING

Front wheel full power hydrostatic system utilising the main hydraulic pump via a steering priority valve. In the event of engine failure, emergency steering is maintained (all models).

ELECTRICAL

130 Ampere-hour 12 V negative ground, utilising wiring and connectors meeting IP69 water ingress test standard. Central fuse panel.

TYRES

Front: 12.5 x 18 -12 PR Rear: 16.9 x 28 -12 PR

All Available Variants: 2DX and 3DX

SHIPPING WEIGHT

7660 kg

WHEELBASE

2.24 m

STANDARD SHOVEL

1.0 cu.m (6-in-1

STANDARD BUCKET CAPACITY

0.26 cu.m

DUMP HEIGHT 2.72 m

2.72 m

LOAD OVER HEIGHT

3.23 m

MAX. DIG DEPTH

MAX. WORKING HEIGHT //

LOADER ARM BREAKOUT FORCE // 4850 kgf

BUCKET TEAROUT FORCE 5700 kgf



Extended warranty up to 3 year





EXPERIENCE THE BEST SERVICE





To know more, visit your nearest dealership.

